Cosmic Origins Program Analysis Group: Status Report Christopher Martin, Chair COFAG Executive Committee

Outline
I. COPAG composition and activities
2. Science Goals
3. Mission/Technology Requirements
4. Burning Issues

COPAG Workshop September 19, 2012

#### I. COPAG Composition and Activities

#### **COPAG Executive Committee**



**Chris Martin** Caltech (Chair)



Ken Sembach StScl



Julianne Dalcanton Paul Goldsmith UWash



JPL



**Chuck Lillie** 



Jon Gardner GSFC



Lynne Hillenbrand Caltech



James Lowenthal Smith College



Paul Scowen ASU



**David Leisawitz GSFC** 

## 2012 Tasks/SAGs

- SAGI: Science Goals, Objectives, Requirements for Cosmic Origins missions. Where are science thresholds and how do they link with Probe vs. Flagship class and aperture size?
- SAG2: Determine technology focus areas for a monolithic 4m Aperture UV/Optical/NIR mission with Internal Coronograph for Exoplanet Imaging
- SAG3: Determine technology focus areas for a segmented 8 m Aperture UV/Optical/NIR mission with External Occulter for Exoplanet Imaging
- SAG4: Determine technology focus areas for future Far IR Instruments
- SAG5: What is the scientific case for a set of linked probes and corresponding technology requirements?

# COPAG Activities 2011-2012

- Draft Technology Assessment → ApS (Oct 19, 2011)
- Winter community workshop Jan 8, 2012 AAS Austin
- Attending PhysPAG meeting DC Aug 14, 2012
- Supporting NASA Cosmic Origins Program Office Science RFI Process
- Workshop at StScI 21 Sept 2012: UVO RFI, Cosmic Origins Science Objectives, Probes

## 2. Developing a Single, Coherent Science Story

# Cosmogony

Following the flow of matter from the Cosmic Web to Planets











Following the flow of Baryons from the Cosmic Web to Planets



## Cosmogony

Following the flow of Baryons from the Cosmic Web to Planets

#### IGM (δ~1-100)

- Where are the baryons?
- How does gas flow from the IGM to the CGM to galaxies?
- How is the IGM affected by the evolution of galaxies and massive black holes over time?
- Does the IGM trace dark matter?





# Cosmogony

Following the flow of Baryons from the Cosmic Web to Planets



# IGM

#### CGM (δ~10<sup>2</sup>-10<sup>4</sup>)

- What are the flows of matter and energy in the circumgalactic medium?
- How do baryons cycle in and out of galaxies?
- What is in the circum-galactic medium?
- How are galaxies fed? How do galaxies acquire their gas across cosmic time?
- How does galaxy feedback work?
- How are the chemical elements dispersed & distributed in the circumgalactic & intergalactic media?
- Where are the baryons?





#### Galaxies ( $\delta \sim 10^4 - 10^8$ )

- How do galaxies build up their stellar component over cosmic time?
- What processes regulate the conversion of gas into stars inside galaxies?
- How are the chemical elements dispersed and distributed in galaxies?
- What is the fossil record of galaxy assembly over cosmic time?

# Cosmogony

Following the flow of Baryons from the Cosmic Web to Planets







#### Clusters/GMCs ( $\delta \sim 10^8 - 10^{10}$ )

IGM

- How do stars form?
- How does gas flow into and control star formation?
- How does feedback control star formation?











#### Science Goals

- **Goal I:** Characterize the growth of large-scale baryonic structures in the intergalactic medium
- **Goal 2:** Observe and explain the assembly of galaxies over cosmic time
- **Goal 3:** Trace and understand the flows of baryons between galaxies and the intergalactic medium
- **Goal 4:** Trace and understand the cycles of matter and energy within galaxies
- **Goal 5:** Measure and explain the history of star formation in galaxies over time
- **Goal 6:** Determine how the conditions for habitability arise during planetary system formation

3. Translating This into Science Measurement Objectives & Technology Requirements

## Science Measurement Objectives

- **Objective I:** Characterize the spatial distribution of IGM absorption lines using background QSOs and galaxies through high resolution UV spectroscopy
- **Objective 2:** High angular resolution UVO imaging and imaging spectroscopy of forming galaxies and galaxy systems
- **Objective 3:** High angular resolution photometry of individual stars in a representative sample of galaxies
- **Objective 4:** UV Imaging spectroscopy of star formation regions, galaxies, CGM and IGM
- **Objective 5:** Multiobject UV spectroscopy of galaxies, CGM, CQM
- **Objective 6:** Wide field UV/optical photometry of star formation regions in nearby galaxies
- **Objective 7:** UV/optical imaging spectroscopy of protostars and Protoplanetary disks
- **Objective 8:** Far IR/sub-mm imaging and spectroscopy of forming galaxies
- **Objective 9:** Far IR/sub-mm imaging and spectroscopy of star formation regions
- **Objective IO:** Far IR/sub-mm imaging interferometric spectroscopy of SFRs, protostars, PPDs

#### Astro 2010 Science Questions → Cosmic Origins Measurements

	0	0	UV		UV		FIR		
COSMOLOGY & FUNDAMENTAL PHYSICS	HCI/S	HRI	WFI	HRS	MOS	IFS	SPICA	10m	IF
HOW DID THE UNIVERSE BEGIN?									
WHY IS THE UNIVERSE ACCELERATING?			x		x				
WHAT IS DARK MATTER?		x	x						
WHAT ARE THE PROPERTIES OF NEUTRINOS?									
GALAXIES ACROSS COSMIC TIME									
HOW DO COSMIC STRUCTURES FORM & EVOLVE?		х	х	х	х	х	х	х	Х
HOW DO BARYONS CYCLE IN & OUT OF GALAXIES, AND WHAT DO THEY DO WHILE THEY ARE THERE?		х	х	х	х	х	х	х	х
HOW DO BLACK HOLES GROW, RADIATE, AND INFLUENCE THEIR SURROUNDINGS?		х	х	х	х	х	х	х	х
WHAT WERE THE FIRST OBJECTS TO LIGHT UP THE UNIVERSE AND WHEN DID THEY DO IT?					х	х	х	х	
GALACTIC NEIGHBORHOOD									
WHAT ARE THE FLOWS OF MATTER & ENERGY IN THE CIRCUMGALACTIC MEDIUM?		х	х	х	х	х	х	х	х
WHAT CONTROLS THE MASS-ENERGY-CHEMICAL CYCLES WITHIN GALAXIES?		х	х		х	х	х	х	х
WHAT IS THE FOSSIL RECORD OF GALAXY ASSEMBLY FROM THE FIRST STARS TO THE PRESENT?		х	х	х	х		х	х	х
WHAT ARE THE CONNECTIONS BETWEEN DARK AND LUMINOUS MATTER?					х	х			
PLANETARY SYSTEMS & STAR FORMATION									
HOW DO STARS FORM?		х	х	х	х	х	х	х	Х
HOW DO CIRCUMSTELLAR DISKS EVOLVE & FORM PLANETARY SYSTEMS?	х	х	х	Х	X?	х	х	х	Х
HOW DIVERSE ARE PLANETARY SYSTEMS?	х								Х
DO HABITABLE WORLDS EXIST AROUND OTHER STARS,& CAN WE IDENTIFY THE TELLTALE SIGNS OF LIFE ON AN EXOPLANET?	х						x	х	х
STARS AND STELLAR EVOLUTION									
HOW DO ROTATION & MAGNETIC FIELDS AFFECT STARS?			х	х	х				
WHAT ARE THE PROGENITORS OF TYPE Ia SUPERNOVAE			х	х	х				
HOW DO THE LIVES OF MASSIVE STARS END?	0.44-0		х			х	х	х	х
WHAT CONTROLS THE MASS, RADIUS, AND SPIN OF COMPACT STELLAR REMNANTS?	9/12	х						2.	5

#### Example: Measurement $\rightarrow$ UV Detector Requirements

UV Detector Property	UV High Resolution/High Contrast Imaging	UV Wide Field Imaging	UV High Resolution Spectroscopy	UV Multi- Object Spectroscopy	UV Integral Field Spectroscopy	Current Performance
QE	Moderate	Moderate	High- Very High	High	High- Very High	Low-Very Low
Format: Number of Pixels	Very High	Very High	High-Very High	High-Very High	High-Very High	High
Photon- counting	xx	X	XXX	XX	XXX	YES
Equivalent background	Low	Moderate	Very Low	Low-Very Low	Very Low	Moderate
Dynamic Range	High	High	Moderate	Moderate	Moderate	Moderate
Radiation Tolerance	Moderate	Moderate	Moderate	Moderate	Moderate	High
Time Resolution	Low	Low	Low	Low	Low	High
Out of Band Rejection	High	High	Moderate	Moderate	Moderate	High

# Technology Figures of Merit

- I. Current and projected (2020, assuming funding as specified below) performance.
  - e.g., for detectors: QE vs. wavelength, internal/dark noise, photon-counting capability, number of pixels/formats/scaleability, energy resolution, dynamic range.
- 2. Implementation and operational issues/risks:
  - e.g., for detectors requirements for cooling, high voltage, required materials/process improvements, red leak/out of band response.
- 3. Cost/time to TRL-6 and leverage:
  - What is the current TRL level, what NASA funding and time is required to reach TRL6,
  - What is the degree of difficulty of these developments
    - for example using the DOD Degree of Difficulty scale
  - What non-NASA astrophysics division resources can be brought to bear to leverage the development>
    - significant industrial involvement and prior investments, cross-division, cross-agency, private-sector investments and applications, existing infrastructure and institutional investment
- 4. Relevance to and impact on possible future missions:
  - Large 4-8 m UVOIR general astrophysics missions, Far IR/Sub mm missions
  - Joint Exoplanet imaging missions & required compatibility technologies

#### **Cosmic Origins Technology Priorities**

- **Priority 1.** These technologies are *"mission enabling"*, and are the highest priority for immediate investment. We provide preliminary roadmaps for these technologies.
- **Priority 2.** These technologies are *"mission enhancing"*. Some early investment should be considered contingent upon science and mission prioritization.
- **Priority 3.** Many interesting and important technologies may be relevant to future CO missions. Some can be developed once mission choices are made. Others may be developed as part of other activities and programs. Still others may be at early stages of readiness and require more basic research support to mature. Level 3 technologies were not included in Table 3.

## **UVOIR** Technologies

#### Table 3 – Cosmic Origins Technology Matrix

Name of technology	High QE, large format photon-counting UV large- format detectors	UV coatings	Large, low-cost, light- weight precision mirrors for Ultra- <u>Stable</u> Large Aperture UV/Optical <u>Telescopes</u>	Deployable light-weight precision mirrors for future <u>Very</u> Large Aperture UV/Optical <u>Telescopes</u>	Very large format, low noise Optical/IR detector arrays	Photon counting Optical/IR detector arrays
Brief description (1024)	Future NASA UV missions, particularly those devoted to spectroscopy, require high quantum efficiency (>50%), low noise (<1e-7 ct/pixel/s), large-format (>4k x \4k) photon-counting detectors for operation at 100-400nm or broader	High reflectivity, highly uniform UV coatings are required to support the next generation of UV missions, including explorers, medium missions, and a UV/optical large mission. High reflectivity coatings allow multiple reflections, extended bandpasses, and accommodate combined UV and high-contrast exoplanet imaging objectives.	Future UV/Optical telescopes will require increasingly large apertures to answer the questions raised by HST, JWST, Planck and Herschel, and to complement the ≥ 30- m ground-based telescopes that will be coming on line in the next decade. Technologies are therefore required that provide a high degree of thermal and dynamic stability, and wave front sensing and control	Future UV/Optical telescopes will require increasingly large apertures to answer the questions raised by HST, JWST, Planck and Herschel, and to complement the ≥ 30- m ground-based telescopes that will be coming on line in the next decade. Technologies are therefore required that provide a high degree of thermal and dynamic stability, and wave front sensing and control	Future NASA Optical/near-IR missions require large format detector arrays mosaicable in formats of ~Gpix, covering wavelengths from the optical to about 2µm.	Future NASA Optical/near-IR missions require large- format, high quantum efficiency, low dark current, and high readout speed photon counting detector arrays.

## **UVOIR** Technologies

Name of technology	High QE, large format photon-counting UV large- format detectors	UV coatings	Large, low-cost, light- weight precision mirrors for Ultra- <u>Stable</u> Large Aperture UV/Optical <u>Telescopes</u>	Deployable light-weight precision mirrors for future Very Large Aperture UV/Optical <u>Telescopes</u>	Very large format, low noise Optical/IR detector arrays	Photon counting Optical/IR detector arrays
Roadmap	<ol> <li>2011-2014: Investigate 2-4 technological approaches. Goal is demonstration of high QE, low/moderate noise, and moderate/high (scaleable) pixel counts</li> <li>2015: Downselect to 2 promising technologies that have reached TRL3-4.</li> <li>2015-2019: Invest in 2 technologies that provide best capabilities for UV imaging and UV spectroscopy. Scale to high/very high pixel counts. Develop low power versions of required electronics.</li> </ol>	<ol> <li>2011-2013: Demonstrate ALD coatings for Al+MgF<sub>2</sub>. Demonstrate reflectivity and compatibility with internal coronograph.</li> <li>2013-15: Demonstrate stability of ALD coatings for exposed optics. Demonstrate compatibility of conventional coatings with internal coronograph.</li> <li>2015-2019: Develop large optics capability for ALD coatings.</li> </ol>	<ol> <li>2011-2015: Demonstrate the technologies required to fabricate 4-m mirror blanks from ULE/Zerodur, Borosilicate and Silicon Carbide</li> <li>Demonstrate the ability to grind and polish mirror blanks to achieve the required mirror figure and surface roughness for an ExoPlanet imaging mission</li> <li>Develop a 4-m monolithic mirror that meets the requirements for a combined UVOIR/ExoPlanet mission</li> </ol>	<ol> <li>2011-2015: Demonstrate the technologies required to fabricate 1.5-m to 3.6-m mirror blanks from ULE/Zerodur, Borosilicate and Silicon Carbide</li> <li>Demonstrate the ability to grind and polish mirror blanks to achieve the required mirror figure and surface roughness for a UVOIR mission</li> <li>Develop mirror segments for an 8.0 to 9.2-m deployable telescope that meets the requirements for a UVOIR mission</li> </ol>	Defer pending mission requirement	<ol> <li>2012: Much of the relevant expertise exists outside</li> <li>NASA. Coordinate a small workshop to survey and assess different approaches.</li> <li>2012-2015: Technology development at a few vendors/labs aimed at demonstrating high QE, high speed, and low dark current photon counting focused on detector materials development and characterization.</li> <li>2015-2019: Focused development at two vendors/labs aiming to develop mega-pixel class photon-counting detector arrays that have been optimized for low background space astronhysics</li> </ol>
Priority	1 – Detectors are at the heart of every instrument. Detector performance shortfalls can only be made up with high cost increases in aperture	1 – Coating developments could extend the range of UV missions to 100 nm. Coating improvements could increase net throughput by 50-100%. Coating improvements could make a joint Exoplanet/ UVOIR mission possible.	1 – Large monolithic high precision mirror is a prerequisite for 4-m mission and may be applicable to 8-m mission. Optics technology drives mission cost and mass.	2 – Deployable large precision mirror may be required for 8-m mission (depending on launch) vehicle. A deployed mirror may require an external occulter and is less compatible with internal coronagraph	2 – Technology is available at TRL6+. Scaling to very high pixel counts is mission enhancing, but requirements and development should be mission driven.	1 – Photon-counting requirement driven by moderate to high resolution spectroscopy, missions travelling beyond the Zodiacal disk, and high time- resolution science or wavefront sensing

#### Technology Matrix (example)

Name of technology	High QE, large format photon-counting UV large-format detectors
Priority	1 – Detectors are at the heart of every instrument. Detector performance shortfalls can only be made up with high cost increases in aperture.
Roadmap	<ol> <li>2011-2014: Investigate 2-4 technological approaches. Goal is demonstration of high QE, low/moderate noise, and moderate/high (scaleable) pixel counts</li> </ol>
	2) 2015: Downselect to 2 promising technologies that have reached TRL3-4.
	<ol> <li>2015-2019: Invest in 2 technologies that provide best capabilities for UV imaging and UV spectroscopy. Scale to high/very high pixel counts. Develop low power versions of required electronics.</li> </ol>

#### Enhancement of Science Impact of Next Generation UV Technologies

Technology	Implementation Approaches	Potential impacts	Mission Enabling Factor
1) Single Photon counting UV Detector	BSMCPs + GaN Photocathodes AR+DD+EMCCDs	Major increase in QE for large format, low background, versatile detectors	5-10*
2) Next Generation UV Coatings	Atomic Layer Deposition	<ul> <li>High reflectivity coatings —&gt; high performance instruments+telescopes</li> <li>Broad-band coatings —&gt; 100-120 nm coverage: key UV range</li> <li>Ultra-uniform coatings —&gt; Joint Exoplanet/UV astrophysics mission</li> </ul>	3‡
3) Next Generation Diffractive optics	Electron beam lithographic patterning	<ul> <li>Arbitrary groove profile and shape</li> <li>High performance spectrographs</li> <li>High efficiency</li> <li>Low scatter</li> <li>Wide-field, multi-object, high efficiency spectrographs</li> </ul>	2-4§
Total Improvement	Data grasp $(A_{eff} \times N_{objects})$ factor	20-250	
Factor	Aperture reduction factor (linear): $F_A$	2-4	
	Cost reduction factor: $F_A^2$	4-16 (e.g., 10B\$ → 600M-2.5B\$)	

## Far IR/Sub mm Technologies

Name of technology	Large format, low noise Far-IR direct detectors	Ultralow-noise Far-IR direct detectors	Large, cryogenic far-IR telescopes	Interferometry for far-IR telescopes	Cryocoolers
Brief description (1024)	Future NASA Far-IR missions require large format detectors optimized for the very low photon backgrounds present in space. Arrays containing up to tens of thousands of pixels are needed to take full advantage of the focal plane available on a large, cryogenic telescope. Detector sensitivity is required to achieve background-limited performance, using direct (incoherent) detectors to avoid quantum-limited sensitivity.	Future NASA Far-IR missions require detectors optimized for the very low photon backgrounds present in space for spectroscopy. Arrays containing up to thousands of pixels are needed to take full advantage of the spectral information content available. Detector sensitivity is required to achieve background-limited performance, using direct (incoherent) detectors to avoid quantum-limited sensitivity.	Large telescopes provide both light gathering power, to see the faintest targets, and spatial resolution, to see the most detail and reduce source confusion. To achieve the ultimate sensitivity, their emission must be minimized, which requires that these telescopes be operated at temperatures that, depending on the application, have to be as low as 4K. Collecting areas on the order of 10m are needed.	Interferometry in the far-IR provides sensitive integral field spectroscopy with sub- arcsecond angular resolution and R ~ 3000 spectral resolution to resolve protoplanetary and debris disks and measure the spectra of individual high-z galaxies, probing way beyond the confusion limits of current and next- generation single-aperture far-IR telescopes. A structurally-connected interferometer would have the aforementioned capabilities. Eventually the formation-flying interferometric telescope envisaged in the 2000 Decadal survey would provide Hubble-class angular resolution, but that is beyond the scope of this technology plan. Telescopes are operated at temperatures that have to be as low as 4K.	Detectors for far-IR and certain X-ray missions require temperatures in the tens of mK. Compact, low- power, lightweight coolers suitable for space flight are needed to provide this cooling. Powerful, efficient cryocoolers are needed to cool the optical components of far-IR telescopes and provide the heat sink for sub- Kelvin coolers.

# Far IR/Sub mm Technologies

Name of technology	Large format, low noise Far-IR direct detectors	Ultralow-noise Far-IR direct detectors	Large, cryogenic far-IR telescopes	Interferometry for far-IR telescopes	Cryocoolers
Roadmap	Presently have working 10-19 W Hz-1/2 detectors in small arrays. Advance TES bolometers and MKIDs in parallel to TRL ~ 5, then downselect to one detector type. Demonstrate multiplexing in arrays of 256 elements for interferometry. Further develop larger arrays for single-aperture telescope mission.	<ol> <li>Grating spectrometer proposed as US instrument on SPICA will require these detectors – the timescale for SPICA has moved to the right since 2010 Decadal report so that there is time for technology development if it is started in a timely manner (2012).</li> <li>Missions beyond SPICA such as SAFIR/CALISTO will have even greater need as background limit will be even lower and they will be capable of handling larger arrays.</li> </ol>	The telescope for SPICA is expected to be provided by ESA based on Herschel experience. For 10m class mission, materials, surface, and metrology must be developed. Note that since telescope will be cooled to approximately 4K, the test and measurement challenge is extreme.	Telescope requirement is modest (1 m diameter) in comparison to single aperture telescope. The technical challenges for far-IR interferometry are detectors and <u>cryocooling</u> . Metrology is easy (1 micron tolerance). JWST will demonstrate wavefront control at 10x shorter wavelengths, where it's harder. The interferometric technique described above is nearly mature and requires only modest funding to complete the maturation to TRL 6 for application on a Probe-class mission.	Pick up from JWST and IXO development efforts. Advance sub-K continuous ADR coolers in parallel with 4 K cryocoolers to satisfy predicted performance requirements for each (heat lift at specified temperature stages). Finally, integrate coolers into a cryo-thermal system and verify system thermal performance in sub- scale models representative of flight-sized elements. For missions further in the future, the impact of larger focal planes should be included in a comprehensive analysis of overall cryogenic system requirements.
Priority	<ul> <li>1 – Enabling for far-IR spatio- spectral interferometry.</li> <li>2 – Required for background- limited photometry and very low-resolution spectroscopy</li> </ul>	1 – Required for dispersive R~1000 spectrometer with cold telescope, required to achieve background-limited spectroscopy	1 – Significant technology deve understanding of capability for l to the point that a decision mad (which is very different) can be	1 – 4 K and sub-K cryocooling technology is enabling for far-IR spatio- spectral interferometry, and enabling or enhancing for a large far-IR single-aperture telescope.	

# 4. Burning Issues

# 3 (Provocative?) Observations

• We (the space astrophysics community as a whole) need to deal with the coming crisis

• We need to change the cost paradigm

• We need to invest (more) in technology

# The Coming Crisis

- The next logical stage is flagships
- Flagships = 10B\$
- NASA Astrophysics Budget = IB\$/yr
- 50% to Flagships → I Flagship/20 years

## The Coming Crisis



## Choices – Word Association Test

#### Large

- Photon-starved
- •Brute-force
- Diffraction limit
- •Detailed study
- •General
- •Sub-optimized
- Low technology risk
- •Old technology
- •Inertia, Inflexible
- •20-30 years
- Monolithic

#### Small

- •Wide-field
- Innovation driven
- •Highly-multiplexed
- •Discovery
- •Focussed
- Optimized
- •Higher technology risk
- •New technology
- •Responsive, flexible
- •5-15 years
- •Synergistic

#### Purpose of this working meeting

- For the purpose of this meeting, a probe is ~I-2 meter aperture, I-2 instruments (definition of instrument is loose)
- Can a scientifically compelling case be made for one or more cosmic origins probes?
  - How many objectives from 2012 UVO RFI can be accomplished by one or more probes?
  - Can science objectives from NWHN, not submitted to RFI, also be accomplished with one or more probes?
- Can a scientifically compelling case be made for a linked series of astrophysics probes?
- If yes, are there technology investments that enable scientifically compelling probe or probes?